

Afriq Water is K-Rain's distributor and warehousing partner in South Africa. K-Rain is one of the world's largest manufacturers of irrigation rotors, sprays, valves, and controllers. K-Rain Irrigation is ideal for residential, commercial, and sports turf applications.

www.afriqwater.co.za

K-Rain Garden Irrigation





Please Note

We can't offer technical help on the K-Rain range, but you can use the code of the product to search for info on it on the K-Rain site, www.krain.com

K-Rain Prices

K-Rain Controllers					
Code	Stations	Type	Indoor / Outdoor	Excl. Price	Incl. Price
3504-220	4	RPS46	Indoor	R 971.73	R 1 117.48
3506-220	6			R 1 020.00	R 1 173.00
3104ID-220	4	PRO LC		R 1 406.43	R 1 617.39
3108ID-220	8			R 1 850.00	R 2 127.50
3112ID-220	12			R 2 610.00	R 3 001.50
3104WID-220	4	PRO LC Wi-Fi Ready		R 1 634.76	R 1 879.97
3108WID-220	8			R 2 083.95	R 2 396.54
3112WID-220	12			R 2 901.33	R 3 336.52
3104-220	4			Outdoor	R 1 469.29
3108-220	8	R 1 807.14	R 2 078.21		
3112-220	12	R 2 821.43	R 3 244.64		
3104W-220	4	PRO LC Wi-Fi Ready	R 1 708.39		R 1 964.65
3108W-220	8		R 2 180.45		R 2 507.52
3112W-220	12		R 3 019.15		R 3 472.02
3202-220	4	PRO EX 2.0 (Wi-Fi-Ready)	R 2 678.57		R 3 080.36
3924-220	24	RPS624	R 7 296.99		R 8 391.54
BLUE-1	1	Wireless Bluetooth (Battery-Powered)	R 2 081.51		R 2 393.74
BLUE-4	4		R 3 747.14	R 4 309.21	
3400-220	99 Zones	Sitemaster 220VAC 2-Wire Decoder		R 27 200.00	R 31 280.00

K-Rain Controller Accessories				
Code	For	Description	Excl. Price	Incl. Price
3205	PRO EX2.0	4 Station Extension Module	R 760.00	R 874.00
3205-14		14 Station Extension Module	R 3 474.29	R 3 995.43
3206		Optional RF Module	R 1 378.57	R 1 585.36
3209		Optional Wi-Fi Hub	R 2 092.86	R 2 406.79
3100-BRIDGE	PRO LC	Wi-Fi Bridge	R 1 997.14	R 2 296.71
3401	Sitemaster	Single Station Controller	R 2 368.57	R 2 723.86
3402		Surge Protector Decoder	R 1 147.50	R 1 319.63
3208-HRS	ALL	Rain Sensor for All Controllers	R 485.71	R 558.57





K-Rain Rotors

Code	Specifications	Excl. Price	Incl. Price
------	----------------	-------------	-------------

RPS75

RPS75	Inlet F Thread BSP	1.9 cm / 3/4"	Retracted Height	18.7 cm	R 186.01	R 213.91
	Nozzles	1 Installed + 11	Shrub Height	19.0 cm		
	Arc Adj Range	40° - 360°	Riser Height	11.1 cm		
	Flow Range	2.6 - 31 l p/m	Pressure Rating	1.4 - 4.8 BAR		
	Spray Radius	6.7 - 15.5 m	Nozzle Trajectory	26°. Low 11°		
RPS75i		With Intelligent Flow Control			R 211.34	R 243.04

RPS75 SELECT

60003	Inlet F Thread NPT	1.9 cm / 3/4"	Retracted Height	18.7 cm	R 235.27	R 270.56
	Nozzles	4 Pre-Installed	Shrub Height	16.8 cm		
	Arc Adj Range	40° - 360°	Riser Height	11.1 cm		
	Flow Range	4.9 - 25.8 l p/m	Pressure Rating	2.1 - 4.8 BAR		
	Spray Radius	10 - 14 m	Percipitation Rate	6 - 20 mm/hr		

MINI PRO GEAR-DRIVE SPRINKLER

13003	Inlet F Thread BSP	1.3 cm / 1/2"	Retracted Height	15.2 cm	R 185.20	R 212.98
	Nozzles	1 Installed + 4	Riser Height	10.2 cm		
	Arc Adj Range	40° - 360°	Nozzle Trajectory	26°		
	Flow Range	3 - 14.4 l p/m	Pressure Rating	1.4 - 4.8 BAR		
	Spray Radius	5.5 - 10.1 m	Percipitation Rate	6.6 - 15.24 mm/hr		

SUPER PRO WITH INTELLIGENT FLOW GEAR DRIVEN SPRINKLER

10003	Inlet F Thread BSP	1.9 cm / 3/4"	Retracted Height	19.05 cm	R 259.94	R 298.93
	Nozzles	1 Installed + 12	Riser Height	10.79 cm		
	Arc Adj Range	40° - 360°	Nozzle Trajectory	26°		
	Flow Range	4.1 - 42 l p/m	Pressure Rating	1.4 - 4.8 BAR		
	Spray Radius	7 - 14 m	Percipitation Rate	5.39 - 30.89 mm/hr		
10003-SH		With Shrub Head			R 287.19	R 330.27

PRO SPORT 4" WITH BSP THREAD

14003-BSP	Inlet F Thread BSP	1"	Retracted Height	19.05 cm	R 810.53	R 932.11
	Nozzles	1 Installed + 12	Riser Height	10.79 cm		
	Arc Adj Range	40° - 360°	Nozzle Trajectory	26°		
	Flow Range	4.1 - 42 l p/m	Pressure Rating	1.4 - 4.8 BAR		
	Spray Radius	7 - 14 m	Percipitation Rate	5.39 - 30.89 mm/hr		
14003-BSP-SS		Stainless Steel Unit			R1007.52	R 1158.65

K1 SMART SET GEAR DRIVE SPRINKLER

31031	Inlet F Thread BSP	1.3 cm / 1/2"	Area Covered	2.78 m ²	R 195.71	R 225.07
	Distance Adj.	Turnable Screw	Riser Height	10 cm		
	Spray Radius	4.5 - 19.1 m	Arc Adj Range	40° - 360°		





K-Rain Rotors Continued

Code	Specifications	Excl. Price	Incl. Price
------	----------------	-------------	-------------

K2 PRO

10031	Inlet F Thread BSP	1.9 cm / 3/4"	Retracted Height	19 cm	R 267.14	R 307.21
	Nozzles	1 Pre-Installed	Shrub Height	N/A. Pop-Up		
	Arc Adj Range	90° - 360°	Riser Height	12.7 cm		
	Flow Range	4 - 42 l p/m	Pressure Rating	2 - 4 BAR		
	Spray Radius	5.5 - 12 m	Percipitation Rate	7 - 17 mm/hr		

DIY K5 SELECT

61031	Inlet F Thread NPT	1.9 cm / 3/4"	Pressure Rating	2 - 3.4 BAR	R 285.49	R 328.32
	Nozzles	4 Pre-Installed	Water-Saving Rate	30% Compared to other rotor systems		
	Arc Adj Range	40° - 360°				
	Flow Range	2.6 - 31 l p/m				
	Spray Radius	10 - 14 m				

DIY K5 GEAR DRIVE SPRINKLER

15103	Inlet F Thread BSP	1.9 cm / 3/4"	Riser Height	10 cm	R 234.09	R 269.21
	Spray Radius	6 - 16.7 m	Arc Adj Range	40° - 360°		

K-Rain Rotor Replacement / Spare Parts / Keys

Code	For	Excl. Price	Incl. Price
P100901	RPS75 DIY K5 Gear Drive - 15103	R 15.50	R 17.83
P100902	PRO-SPORT 14003-BSP & 14003-BSP-SS RPS SELECT - 60003 SUPER PRO 10003 & 10003-SH DIY K5 Gear Drive - 15103	R 16.43	R 18.89
P59995	MINI PRO 13003 K ROTORS (K1 31031 & K2 10031 & K5 61031)	R 16.43	R 18.89

ELECTRIC VALVES

Code	Specifications	Excl. Price	Incl. Price
------	----------------	-------------	-------------

PRO SERIES 100 VALVE

24V AC 60 Cycle Solenoid | Inrush Current 0.43 Amps | Holding Current 0.25 Amps

7001-BSP	Female BSP	2.5 cm / 1"	Pressure Rating	1.4 - 10.3 BAR	R 316.43	R 363.89
	Flow Control	Manual	Flow Range	18.9 - 113.6 l p/m		

PRO SERIES 150 VALVE

24V AC 60Hz Standard Solenoid | Inrush Current 0.43 Amps | Holding Current 0.25 Amps
MAX 10.3 BAR Pressure Rating

7101-BSP	Female BSP	2.5 cm / 1"	Flow Range	18.9 - 113.6 l p/m	R 295.00	R 339.25
7101-BSP-FC	PRO SERIES 150 VALVE 2.5 cm / 1" With Flow Control				R 351.36	R 404.06
7115-BSP	Female BSP	3.8 cm / 1/2"	Flow Range	75.7 - 454.2 l p/m	R 1 278.57	R 1 470.36
7102-BSP	Female BSP	5 cm / 2"	Flow Range	75.7 - 454.2 l p/m	R 1 427.86	R 1 642.04





K-Rain Sprayers

Code	Specifications				Excl. Price	Incl. Price
PRO-S						
Inlet F BSP 1.3 cm / 1/2" Pressure Rating 1.4 - 7.6 BAR Flow Range 0.76 ℓ p/m @ 6 BAR						
78004	Type	4"	Retracted Height	15.2 cm	R 38.56	R 44.34
	Side Inlet	No	Riser Height	8.9 cm		
78012	Type	12"	Retracted Height	40.6 cm	R 203.57	R 234.11
	Side Inlet	Yes	Riser Height	29.2 cm		
24151-H	Type	4" with KVF15 Noz	Retracted Height	15.2 cm	R 73.54	R 84.57
	Side Inlet	No	Riser Height	8.9 cm		
	Spray Radius	4.27 - 5.18 m	Flow Range	2.84 - 17.41 ℓ p/m		
78000	PRO-S SPRAYERS NOZZLE GUARD (78004 / 780012 / 24151-H)				R 16.43	R 18.89

ST-IS SURE THROW IMPACT SPRINKLER PART CIRCLE

ST-IS45	Inlet F Thread NPT	1.3 cm / 1/2"	Retracted Height	23.9 cm	R 269.92	R 310.41
	Nozzles	1 Pre-Installed + 3	Riser Height	6.5 cm		
	Arc Adj Range	15° - 360°	Nozzle Trajectory	26°		
	Flow Range	7.6 - 19.9 ℓ p/m	Pressure Rating	2 - 3.9 BAR		
	Spray Radius	11.3 - 12.8 m	Percipitation Rate	7 - 17 mm/hr		
ST-IS45-TOOL		ST-IS45 ADJUSTMENT TOOL			R 192.86	R 221.79

NARROW PROFILE (NP) SPRAYER BODIES

Inlet F BSP 1.3 cm / 1/2" | Pressure Rating 1.4 - 3.5 BAR
Ratcheting Riser | Stainless Steel Retraction Spring

NP2	Retracted Height	10.2 cm	Riser Height	5.1 cm	R 38.21	R 43.95
NP4	Retracted Height	15.2 cm	Riser Height	9.8 cm	R 38.21	R 43.95

NARROW PROFILE (NP) 4" SPRAYERS WITH KVF NOZZLES 90° - 360°

NP4-KVF6 ●	Spray Radius	1.82 - 2.74 m	Flow Range	1.2 - 6 ℓ p/m	R 40.13	R 46.15
NP4-KVF8 ●	Spray Radius	2.74 - 3.05 m	Flow Range	1.48 - 8.71 ℓ p/m	R 40.13	R 46.15
NP4-KVF10 ●	Spray Radius	3.05 - 3.66 m	Flow Range	1.7 - 10.6 ℓ p/m	R 40.13	R 46.15
NP4-KVF12 ●	Spray Radius	3.66 - 4.27 m	Flow Range	2.46 - 13.25 ℓ p/m	R 40.13	R 46.15
NP4-KVF15 ●	Spray Radius	4.27 - 5.18 m	Flow Range	2.84 - 17.41 ℓ p/m	R 40.13	R 46.15
NP4-KVF17 ●	Spray Radius	5.18 - 5.49 m	Flow Range	3.22 - 18.17 ℓ p/m	R 40.13	R 46.15

K-Rain Nozzles

KVF NOZZLES 90° - 360°

Code	Specifications				Excl. Price	Incl. Price
KVF6 ●	Spray Radius	1.82 - 2.74 m	Flow Range	1.2 - 6 ℓ p/m	R 21.61	R 24.86
KVF8 ●	Spray Radius	2.74 - 3.05 m	Flow Range	1.48 - 8.71 ℓ p/m	R 21.61	R 24.86
KVF10 ●	Spray Radius	3.05 - 3.66 m	Flow Range	1.7 - 10.6 ℓ p/m	R 21.61	R 24.86
KVF12 ●	Spray Radius	3.66 - 4.27 m	Flow Range	2.46 - 13.25 ℓ p/m	R 21.61	R 24.86
KVF15 ●	Spray Radius	4.27 - 5.18 m	Flow Range	2.84 - 17.41 ℓ p/m	R 21.61	R 24.86
KVF17 ●	Spray Radius	5.18 - 5.49 m	Flow Range	3.22 - 18.17 ℓ p/m	R 21.61	R 24.86





K-Rain Nozzles Continued

Code	Specifications	Excl. Price	Incl. Price
------	----------------	-------------	-------------

Rotary Hand Adjustable Nozzles

Flow Control (25% Radius Reduction) 80° - 360° | Double Pop-Up System | Speed Rotation Control | Multiple Stream Technology | Low flow rate | 2.8 Recommended BAR

RN100-ADJ	Spray Radius	3.9 - 4.5 m	Flow Rate	0.83 - 4.50 ℓ p/m	R 130.12	R 149.64
RN200-ADJ	Spray Radius	4.8 - 5.7 m	Flow Rate	1.29 - 7.19 ℓ p/m	R 130.12	R 149.64
RN300-ADJ	Spray Radius	7.9 - 8.5 m	Flow Rate	3.03 - 14.38 ℓ p/m	R 130.12	R 149.64

Fixed Pattern Nozzles

1.5 - 2 Recommended BAR

Centre-Strip						
FN15CS	Spray Radius	1.2 - 9.1 m	Flow Rate	3 - 3.8 ℓ p/m	R 23.91	R 27.50
End-Strip						
FN15ES	Spray Radius	1.2 - 4.6 m	Flow Rate	1.5 - 1.9 ℓ p/m	R 23.91	R 27.50
Side-Strip						
FN15SS	Spray Radius	1.2 - 9.8 m	Flow Rate	4.2 - 4.9 ℓ p/m	R 23.91	R 27.50

K-Rain Installation Accessories

Code	Description	Excl. Price	Incl. Price
P3008114	9V Replacement Solenoid	R 281.24	R 323.43
P3008113	24V Replacement Solenoid	R 251.10	R 288.76
P3004750	24V Replacement Solenoid Kit for RainBird / Hunter	R 401.88	R 462.16
P513995	MINI PRO / 13003 Check Disc with Insert	R 32.95	R 37.89
P16009110	1.9 cm / 3/4" Rotor Check Disc with Insert	R 17.29	R 19.89
P53428	Pro-S Spray Check Valve	R 26.07	R 29.98
P53429	NP Spray Check Valve with Insert	R 20.90	R 24.04
PFSA	Adaptor Shrub with Male Thread	R 16.07	R 18.48
1522	2.2kW 220V Pump-Start Relay	R 1 332.84	R 1 532.77
TB-ADJ	Adjustable Tree Bubblers 0 - 20 ℓ p/m	R 36.00	R 41.40

